

Product Datasheet

Jacketed and insulated safety shower with body spray

EXP-EJ-5GS/10G

In locations susceptible to the effects of direct sunlight, this floor mounted jacketed and pre-insulated emergency safety shower helps protect the pipework. Featuring an overhead shower complemented by a body spray for additional targeted drenching towards the lower part of the body. Meets EN15154 and ENZ358.1-2014 requirements.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER NOZZLE	Injection moulded nylon 6
BODY SPRAY	uPVC
INSULATION & OUTER CASING	Polyurethane foam insulation with a medium density polyethylene impact resistant outer casing
SERVICES	
WATER INLET	1¼" male BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower/body spray: 115 L per minute / 30 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	0C / 32F
MAXIMUM	55C / 131F
OPERATION	
SHOWER/BODY SPRAY	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	320mm (8.3in) x 890mm (35in) x 2330mm (91.7in)
WEIGHT	22kg (49lb)

General Arrangement Drawing

Jacketed and insulated safety shower with body spray

EXP-EJ-5GS/10G

