

Product Datasheet

Wall mounted laboratory safety shower

LAB-23GS/H

In a laboratory situation where floor space is at a premium, this wall mounted unit provides a compact fix. Corrosive or flammable materials encountered in the lab are no problem as the green powder coated stainless steel pipework allows for increased resistance. Designed to meet the requirements of the European Standard EN15154 for Laboratories and ANSI Z358.1-2014.



Specifications

| MATERIALS OF CONSTRUCTION | |
|-------------------------------|--|
| PIPEWORK & FITTINGS | Stainless steel |
| OPERATING VALVE | Stainless steel |
| SHOWER ROSE | Powder coated stainless steel |
| STANDARD FINISH | Green powder coated polyester |
| SERVICES | |
| WATER INLET | 1" male BSP |
| OPERATING PRESSURE | 2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve) |
| MINIMUM FLOW RATES | 76 L per minute / 20 US gal per minute |
| AMBIENT OPERATING TEMPERATURE | |
| MINIMUM | 5C / 41F |
| MAXIMUM | 35C / 95F |
| OPERATION | |
| SHOWER | Pull handle |
| DIMENSIONS & WEIGHT | |
| DIMENSIONS (WxDxH) | 260mm (10.6in) x 805mm (31.7in) x 230mm (9.1in) |
| WEIGHT | 5kg (11lb) |

General Arrangement Drawing

Wall mounted laboratory safety shower

LAB-23G/H

LAB-23GS/H

