

Product Datasheet

Removable insulated, or heated and insulated jackets for the Optiwash®

Retrofittable jackets designed for use with the Optiwash self-contained eye wash when located outdoors. The insulated jacket offers protection both from the the frost and solar radiation, while the heated jacket provides freeze protection down to -34C (-30F).

The Optiwash is ideal where a continuous supply of water is not available. The 38 litre, wall-mounted eye wash station delivers a controlled flow of a minimum 1.5 litres per minute of potable water for 15 minutes, meeting EN15154 and ANSI Z358.1-2014 requirements.



Specifications

GENERAL SPECS AND INSULATED JACKET	
OUTER FABRIC	PE560, grey and green PVC coated polyester
INSULATION	12mm needle felt
INNER FABRIC	Silicone coated glass cloth
FASTENINGS	FR hook and loop with draw cord
DOCUMENT POUCH	Zipped A4
DIMENSIONS - PACKAGED (WxDxH)	762mm (30in) x 508mm (20in) x 102mm (4in)

NON-FLAMEPROOF HEATED AND INSULATED JACKET	
VOLTAGE	230V (110V available upon request)
POWER RATING	60W
HEAT SOURCE	Self-regulating trace tape heating
CONNECTING CABLE	2m x 3 core cable
POWER CONNECTION	Supplied with flying lead

FLAMEPROOF (ATEX) HEATED AND INSULATED JACKET	
ELECTRICAL EQUIPMENT	ATEX Zone 1 & 2. ATEX gas zone II 2G IIA & IIB T3 X and ATEX dust zone II 2D IIIC T135 X
VOLTAGE	230V (110V available upon request)
POWER RATING	60W
HEAT SOURCE	Self-regulating trace tape heating
POWER CONNECTION	Wall mounted junction box with cable entry size M20 x 1.5