

# Product Datasheet

## Ceiling mounted unheated safety shower

EXP-23G/V  
EXP-23GS/V

For areas with limited floor space, this ceiling mounted option is an excellent choice.

Designed in accordance with EN and ANSI standards it is capable of delivering a drenching of water at 76 litres per minute in the event of an emergency. This unheated emergency safety shower is simple to operate using the pull rod for instant activation.



## Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (GS) or galvanised mild steel (G)
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER NOZZLE	Injection moulded nylon 6
STANDARD FINISH	Polished brush (GS) or green powder coated (G)
SERVICES	
WATER INLET	1" female BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	76 L per minute / 20 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER/BODY SPRAY	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	150mm (5.9in) x 219mm (8.6in) x 802mm (31.6in)
WEIGHT	5kg (11lb)

# General Arrangement Drawing

## Ceiling mounted unheated safety shower

EXP-23G/V  
EXP-23GS/V

