

# Product Datasheet

## 1200L Tank fed safety shower - jacketed & insulated

### J14KS1200

Effective in environments where a constant supply of water cannot be guaranteed. Equally, if there is insufficient water pressure or inadequate flow rates this 1200 liter (317 US gal) tank fed safety shower is essential.

For outdoor use in hot climates, the addition of a chiller unit is crucial to prevent water within the tank reaching dangerous levels and potentially scalding a casualty upon activation.

For indoor use, this jacketed and insulated model assists in maintaining a steady water temperature within the tank. Features internally mounted, covered eye/face wash unit.

Note: this tank shower is ANSI compliant for the 15 minutes time requirement only when connected to a plumbed-in water source.



Shown with optional GRP panels and foot panel activation

## Specifications

MATERIALS OF CONSTRUCTION	
FRAME AND LEGS	Stainless steel
WATER TANK	1200 L (317 US gal) capacity medium density polyethylene MDPE
TANK SURROUND AND LID	GRP
PIPING AND VALVE	uPVC and stainless steel
SHOWER CONTROL VALVE	uPVC 1½" ball valve
EYE WASH CONTROL VALVE	½" stainless steel full flow ball valve
EYE WASH DIFFUSERS	uPVC
EYE WASH STRAINER	½" stainless steel
BALLCOCK VALVE	2 x ½" brass
OVERFLOW	1" female NPT uPVC
SHOWER ROSE	GRP, stainless steel
PANIC BAR	Red powder coated stainless steel
FOOT CONTROL OPTIONS	GRP panel (for shower) and powder coated stainless steel treadle (for eye wash)
FASTENERS AND FIXINGS	Stainless steel
SERVICES	
WATER INLET	¾" female NPT
OPERATING PRESSURE	0.5 to 7 BAR G / 7 to 101 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye/face wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	1C / 34F
MAXIMUM	35C / 95F (+55C (131F) with optional chiller unit)
OPERATION	
SHOWER	Push activated panic bar or optional GRP foot panel
EYE WASH	Lift lid
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	1346mm (53in) x 1498mm (59in) x 3632mm (143in)
WEIGHT	340kg (750lb)

# HUGHES



HUGHES-SAFETY.COM

Justrite Safety Group

www.hughes-safety.com

# General Arrangement Drawing

## 1200L Tank fed safety shower - jacketed & insulated

J14KS1200

