

Product Datasheet

2000L Tank fed safety shower - jacketed & insulated

J14KS2000

Featuring a self-contained tank there is no need for a mains water supply making this the best solution for remote locations. For indoor use, this jacketed and insulated model assists in maintaining a steady water temperature within the tank shower.

For outdoor use in hot climates, adding a chiller unit is crucial to prevent water within the tank from reaching dangerous levels and potentially scalding a casualty upon activation. The integral immersion heater and thick polyurethane insulation maintain a safe water temperature within the overhead tank.

Features internally mounted, covered eye/face wash unit and rectangular hollow section stainless steel frames designed and built to be earthquake-proof, conforming to the California Building Code.



Shown with optional GRP panels and hands-free foot activation

Specifications

MATERIALS OF CONSTRUCTION	
FRAME AND LEGS	Stainless steel
WATER TANK	2000 L (528 US gal) capacity medium density polyethylene MDPE
TANK SURROUND AND LID	GRP
PIPING AND VALVE	uPVC and stainless steel
SHOWER CONTROL VALVE	uPVC 1½" ball valve
EYE WASH CONTROL VALVE	½" stainless steel full flow ball valve
EYE WASH DIFFUSERS	uPVC
EYE WASH STRAINER	½" stainless steel
BALLCOCK VALVE	2 x ½" brass
OVERFLOW	1" male uPVC
SHOWER ROSE	GRP, stainless steel
PANIC BAR	Red powder coated stainless steel
FOOT CONTROL OPTIONS	GRP panel (for shower) and powder coated stainless steel treadle (for eye wash)
FASTENERS AND FIXINGS	Stainless steel
SERVICES	
WATER INLET	¾" female NPT (interior), 2" female NPT (exterior)
OPERATING PRESSURE	0.5 to 7 BAR G / 7 to 101 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye/face wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	1C / 34F
MAXIMUM	35C / 95F (+55C (131F) with optional chiller unit)
OPERATION	
SHOWER	Push activated panic bar (or optional GRP foot panel)
EYE WASH	Lift lid
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	2057mm (81in) x 1498mm (59in) x 3759mm (148in)
WEIGHT	450kg (992lb)

HUGHES



HUGHES-SAFETY.COM

Justrite Safety Group

www.hughes-safety.com

General Arrangement Drawing

2000L Tank fed safety shower - jacketed & insulated

J14KS2000

