

# Product Datasheet

## 2000L Tank fed safety shower with doors - immersion heated MH14KS2000P

Designed for severely cold climates this 2000 liter (528 US gal) gravity fed tank shower incorporates a double-skinned fiberglass, insulated cubicle to protect the user from the elements in the event of an emergency. Featuring a self-contained tank there is no need for a mains water supply making this a great solution for remote locations.

Meets and exceeds ANSI standards by providing tepid water for over 15 minutes at a guaranteed flow of 76 liters (20 US gal) per minute.



## Specifications

MATERIALS OF CONSTRUCTION	
FRAME AND LEGS	Stainless steel
WATER TANK	2000 L (528 US gal) capacity heavy density polyethylene HDPE
TANK SURROUND AND LID	GRP
INSULATION	40mm (1½") foil backed polyurethane
PIPING AND VALVE	uPVC and stainless steel*
SHOWER CONTROL VALVE	uPVC 1½" ball valve*
EYE WASH CONTROL VALVE	½" stainless steel full flow ball valve
EYE WASH STRAINER	½" stainless steel
BALLCOCK VALVE	2 x ½" brass*
OVERFLOW	1" male uPVC*
SHOWER ROSE	GRP, stainless steel
PANIC BAR	Red powder coated stainless steel
FOOT CONTROL OPTIONS	GRP panel (for shower) and powder coated stainless steel treadle (for eye wash)
FASTENERS AND FIXINGS	Stainless steel
SERVICES	
ELECTRICAL EQUIPMENT	General purpose or CLASS 1, DIV 2, GRPS C&D
ELECTRICAL SUPPLY	110V, single phase, 50/60Hz, 1.7kW (220V optional)
IMMERSION HEATER RATING	1.7kW (2.5kW for 220V)
WATER INLET	¾" female NPT
OPERATING PRESSURE	0.5 to 7 BAR G / 7 to 101 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye/face wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	-35C / -31F
MAXIMUM	35C / 95F

\* all stainless steel piping and valves available as an option

Specifications continued overleaf

# General Arrangement Drawing

## 2000L Tank fed safety shower - immersion heated

MH14KS2000

### Specifications cont.

OPERATION	
SHOWER	Push activated panic bar (or optional foot panel)
EYE WASH	Lift lid (or optional foot treadle)
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	2057mm (81in) x 1498mm (59in) x 3937mm (155in)
WEIGHT	Empty: 618Kg Full: 2618Kg

