

Product Datasheet

Pedestal mounted eye wash with ABS closed bowl

45GP
45GSP

For fast and convenient relief in an emergency this pedestal mounted eye/face wash with ABS lidded bowl is a great option for indoor use. The pedestal pipework is available in a choice of stainless steel or galvanized mild steel. Activation is simple, either pull down the lid or utilize the optional hands-free foot treadle. Designed in accordance with ANSI Z358.1-2014 standards.



Shown with optional foot treadle

Specifications

MATERIALS OF CONSTRUCTION	
BOWL/LID	Acrylic capped ABS
DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
PIPEWORK	Stainless steel (GS) or galvanized mild steel (G)
STANDARD FINISH (G)	Green powder coated (G) Polished brush finish (GS)
SERVICES	
WATER INLET	1 1/4" Female NPT
OPERATING PRESSURE	2.0 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
EYE/FACE WASH	Pull lid down (optional foot treadle control for hands free operation)
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	501mm (19.7in) x 464mm (18.3in) x 1183mm (46.6in)
WEIGHT	10kg / 22lb

General Arrangement Drawing

Pedestal mounted eye wash with ABS closed bowl

45GP
45GSP

